

CONDENSER HEAT PUMP - PERFORMANCE

HEAT EXCHANGER: B26Hx34/1P

SWEP SSP G8 2022.824.1.0

Date: 01/10/2022

SSP Alias: B26-NHP

DUTY REQUIREMENTS		Side 1	Side 2
Fluid		R410A	Water
Flow type		Counter-Current	
Circuit		Inner	Outer
Heat load	kW		14.00
Inlet vapor quality		1.000	
Outlet vapor quality		0.000	
Inlet temperature	°C	60.00	43.00
Condensation temperature (dew)	°C	51.67	
Subcooling	K	3.00	
Outlet temperature	°C	48.57	50.00
Flow rate	kg/s m³/h	0.09140	1.741
Fluid condensed	kg/s	0.09140	

PLATE HEAT EXCHANGER		Side 1	Side 2
Total heat transfer area	m²		1.31
Heat flux	kW/m²		10.7
Mean temperature difference	K		4.44
O.H.T.C. (available/required)	W/m²,°C		2400/2400
Pressure drop - total*	kPa	5.91	4.77
- in ports (Inlet/Outlet)	kPa	-0.0891/0.0877	0.335
Operating pressure (outlet)	kPa	3170	
Number of channels per pass		16	17
Number of plates			34
Oversurfacing	%		0
Fouling factor	m²,°C/kW		0.000
Port diameter (up/down)	mm	24.0/18.0	27.0/27.0
Recommended inlet connection diameter	mm	5.91 - 13.2	
Recommended outlet connection diameter	mm	8.05 - 16.1	
Reynolds number			857.4
Inlet Port velocity	m/s	1.51	0.844
Channel velocity	m/s	0.270	0.180
Shear stress	Pa		9.40
Largest wall temperature difference	K		0.22
Min./Max. wall temperature	°C	44.33/51.67	44.23/51.53

*Excluding pressure drop in connections.

PHYSICAL PROPERTIES		Side 1	Side 2
Reference temperature	°C	51.62	46.50
Liquid • Dynamic viscosity	cP	0.0796	0.581
• Density	kg/m³	897.9	989.6
• Heat capacity	kJ/kg,°C	2.356	4.180
• Thermal conductivity	W/m,°C	0.07900	0.6393
Vapor • Dynamic viscosity	cP	0.0146	
• Density	kg/m³	133.5	
• Heat capacity	kJ/kg,°C	1.693	
• Thermal conductivity	W/m,°C	0.01407	
• Latent heat	kJ/kg	132.7	
Film coefficient	W/m²,°C	4900	6900

TOTALS	Side 1	Side 2
--------	--------	--------




TOTALS

		Side 1	Side 2
Total weight (no connections)*	kg	5.15 - 5.42	
Hold-up volume (Inner Circuit)	dm ³	0.7	
Estimated refrigerant charge	kg	0.22	
Hold-up volume (Outer Circuit)	dm ³	1.12	
Port size F1/P1	mm	24	
Port size F2/P2	mm	27	
Port size F3/P3	mm	18	
Port size F4/P4	mm	27	
Carbon footprint	kg	36.2	

*Weight depends on the selected product.

DIMENSIONS



A	mm	376 ±1
B	mm	119 ±1
C	mm	329 ±1
D	mm	72 ±1
E	mm	20 (opt. 45) ±1
F*	mm	58.74 - 62.74 +1.5%/-3.5%
G*	mm	4 - 6 ±1
O	mm	2
R	mm	23

*Dimensions depend on the selected product.

*This is a schematic sketch. For correct drawings please use the order drawing function or contact your SWEP representative.

Disclaimer:

Data used in this calculation is subject to change without notice. SWEP strives to use "best practice" for the calculations leading to the above results. Calculation is intended to show thermal and hydraulic performance, no consideration has been taken to mechanical strength of the product. Product restrictions - such as pressure, temperatures and corrosion resistance- can be found in SWEP product sheets and other technical documentation. SWEP may have patents, trademarks, copyrights or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from SWEP, the furnishing of this document does not give you any license to these patents, trademarks, copyrights, or other intellectual property. To the maximum extent permitted by applicable law, the software, the calculations and the results are provided without warranties of any kind, whether express or implied. No advice or information obtained through use of the software (including information provided in the results), will create any warranty not expressly stated in the applicable license terms. Without limiting the foregoing, SWEP does not warrant that the content (including the calculations and the results) is accurate, reliable or correct. SWEP does not warrant that any system comprising heat exchanger and other components, installed on the basis of calculations in this software, will meet your requirements or function to your satisfaction or expectations.

